







# C.o.S.H.H. Regulations (M.S.D.S.)

In response to your request we have pleasure in supplying you with what we understand to be the appropriate and current information we have on the specific products required.

This file covers the following product code/s:

Guilbert Office Depot Viking 160712

C.o.S.H.H. – Control of Substances Hazardous to Health Regulations 1999

M.S.D.S. - Material Safety Data Sheet

### **Product Information Sheet**

### 1. Article and Corporate Identification

Product: Epson Ribbon Cartridge

Manufacturer/Distributor:

TEL: +81-263-52-2552

FAX: +81-263-53-3702

Medical Emergency Number: Not available

### 2. Composition Information

This is an ink formulation

Ink Composition	CAS No.	% By Weight
Carbon black	1333-86-4	< 5 %

Proprietary dyes and pigments	323	1 – 20 %
Proprietary organic materials	(4)	balance

The ink is soaked into nylon or film ribbon.

### 3. Hazard Identification

Not enough data for hazardous classification

3.1 Emergency Overview: Ink component is a yellow, red, blue and black liquid that may cause eye irritation. Avoid contact with eyes or clothing. In the case of skin contact, wash with soap and water. Keep out of reach of children.

### 3.2 Potential Health Effects:

Eyes: Ink contact with eye may be mildly irritating. See Section 11 for Toxicology.

# **EPSON**

Skin: Ink contact with skin may cause irritation, swelling, or redness. It is not

expected to cause an allergic skin reaction. See Section 11 for Toxicology.

Inhalation: Intentional exposure to ink vapors may cause respiratory irritation. See Section

11 for Toxicology.

Ingestion: May cause upset stomach. See Section 11 for Toxicology.

### 4. First Aid Measures

4.1 Eyes: Immediately flush with room temperature, low pressure, clean water for at least

15 minutes. Seek medical attention if eye irritation continues.

4.2 Skin: Wash surface areas with soap and water. Wash soiled clothing before

rewearing. Consult a physician if irritation continues.

4.3 Inhalation: Remove subject to ventilated fresh air. Consult physician if necessary.

4.4 Ingestion: Seek medical advise; and attention if stomach continues to be upset.

### 5. Fire Fighting Measures

5.1 Flammability: Unknown

Chikhowhi

5.2 Extinguishing Media: Water, carbon dioxide, foam or dry chemical

5.3 Fire Fighting Instructions: Use breathing apparatus.

### Accidental Release Measures

Should wear gloves to avoid ink sticking on hands. Rake up by hands, wipe off with cloth.

### Precautions for Safe Handling and Use

Keep out of reach of children. Do not store the cartridge in high or freezing temperatures. Keep cartridge out of direct sunlight. Do not dismantle cartridge. Do not store cartridges with oxidizing agents or explosives. Make sure cartridge is dry before insertion into printer housing.

### 8. Exposure Controls and Personal Protection

8.1 Engineering Controls: None required

8.2 Exposure Controls: None required

8.3 Personal Protection: None required when cartridges are used as intended

### 9. Physical and Chemical Properties of Ink Formulation

Appearance:

Nylon 66 fabric with 4 color ink

Odor:

None

pH:

Not applicable

Boiling point:

Over then 200 °C / 392 °F

Melting point:

No data available

Flash point:

Unknown

Autoflammability:

No data available

Explosive properties: Oxidizing properties: None None

Vapor density: Relative density: Unknown About 1

Solubility in water: Solubility in fat:

Very low No data available

Partition coefficient:

No data available

### 10. Stability and Reactivity

Stability:

Stable

Hazardous polymerization:

Will not occur

Hazardous decomposition products:

None

Incompatible materials:

Oxidizers and explosives

### 11. Toxicology and Health Hazards

Routes Of Overexposure: Eye, skin, inhalation, and oral

### Acute Health Hazards:

- · Overexposure of eye surface to ink may be mildly irritating
- · Overexposure of skin to ink contact may cause irritation and in some people swelling and redness
- · Intentional inhalation overexposure to ink vapors may result in respiratory tract irritation
- · Intentional or accidental oral ingestion may cause an upset stomach

Chronic Health Hazards: None known

Carcinogenicity:

With excessive exposure, carbon black has been listed as a possible human carcinogen. However, as engineered within this ribbon cartridge, emissions to air of carbon black during normal printing use have not been found. IARC, the International Agency for Research on Cancer, has found printing inks to be not

classifiable as human carcinogens.

Mugtagenicity: composition ink None (by Ames Test)\*

\* according to similar

HA Regulated? Orbidia TOLERO ot Established Unknown

> PIS form-RC2 Page 3 of 4

Release Date

# **EPSON**

Eye irritating:

Unknown

Skin irritating:

Unknown

Skin sensitizing:

Unknown

### 12. Ecological Information

No data available on the adverse effects of this material on the environment

### 13. Disposal Considerations

Disposal should be in accordance with national and local requirements.

### 14. Transportation Information

Not regulated as dangerous preparation under Council Directive 88/379/EEC Not regulated as a Hazardous Material by DOT, IMO, or IATA

15.

# **EPSON**

### Regulatory Considerations

Dangerous Preparation? NO
U.S. DOT Hazard Class Regulated? NO
U.S. OSHA Inhalation Hazard? NO
In U.S., NFPA/HMIS Hazard Rating: Unknown

### 16. Other Information

This "Product Information Sheet" contains health, safety, and environmental information. It does not replace any precautionary language or use and disposal information which accompanies the product. The information contained herein is believed to be accurate at the time of preparation, but should only be used as a guide. It is subject to revision from time to time. EPSON does not warrant the completeness or accuracy of the information contained herein.

In consideration of our environment and world neighbors, all genuine EPSON ribbon cartridges are engineered and based on an "Ecologically Friendly" water based technology. EPSON ribbon cartridges contain no CFCs or harsh liquid solvents.

"Wait until you see it in EPSON COLOR"